Serial No.: 09/767,651 U.S. PTO Customer No. 25280

Inventor(s): Willauer et al. Case No.: 5132

AMENDMENTS TO THE CLAIMS

WHAT IS CLAIMED IS:

1-23 (Cancelled)

5

10

20

24. (Currently Amended) A method of forming a three dimensional camouflage textile, comprising the steps of:

forming a base textile <u>with yarns</u> having a thermoplastic material therein; applying a camouflage pattern to the base textile;

forming flat regions and wrinkled regions in the base textile, the flat regions being formed by the application of a hot fluid stream to the yarns having a thermoplastic material and the wrinkled regions being formed by the shrinking of the yarns having a thermoplastic material due to the application of the hot fluid stream.

- 25. (Original) The method according to Claim 24, wherein said step of forming the base textile comprises weaving the base textile.
- 15 26. (Original) The method according to Claim 25, wherein the step of weaving the base textile includes weaving the base textile in a plain weave pattern.
 - 27. (Original) The method according to Claim 25, wherein the step of weaving the base textile includes weaving the base textile in a satin weave pattern.
 - 28. (Original) The method according to Claim 24, wherein said step of forming the base textile comprises knitting the base textile.
 - 29. (Original) The method according to Claim 24, wherein said step of forming the base textile comprises forming the base textile as a nonwoven material.
 - 30. (Cancelled)
- 31. (Original) The method according to Claim 24, wherein said step of forming the flat and wrinkled regions includes orienting hot fluid streams in a row adjacent to the base textile, and creating a relative movement between the base textile and the row of hot fluid streams.

Serial No.: 09/767,651 U.S. PTO Customer No. 25280

Inventor(s): Willauer et al. Case No.: 5132

32. (Original) The method according to Claim 24, further including the said disposing a finishing lubricant on the base textile prior to forming the flat and wrinkled regions.

33. (Currently Amended) A method of forming a three dimensional camouflage textile, comprising the steps of:

forming a base textile <u>with yarns</u> having a thermoplastic material and a camouflage pattern therein; and

forming flat regions and wrinkled regions in the base textile, the flat regions being formed by the application of a hot fluid stream to the yarns having a thermoplastic material and the wrinkled regions being formed by the shrinking of the yarns having a thermoplastic material due to the application of the hot fluid stream.

- 34. (Original) The method according to Claim 33, wherein said step of forming the base textile comprises weaving the base textile.
- 35. (Currently Amended) The method according to Claim 34, wherein the step of weaving the base textile includes weaving the base textile in a plain weave pattern.
 - 36. (Original) The method according to Claim 34, wherein the step of weaving the base textile includes weaving the base textile in a satin weave pattern.
 - 37. (Original) The method according to Claim 33, wherein said step of forming the base textile comprises knitting the base textile.
- 20 38. (Original) The method according to Claim 33, wherein said step of forming the base textile comprises forming the base textile as a nonwoven material.
 - 39. (Cancelled)

5

10

15

25

- 40. (Original) The method according to Claim 33, wherein said step of forming the flat and wrinkled regions includes orienting hot fluid streams in a row adjacent to the base textile, and creating a relative movement between the base textile and the row of hot fluid streams.
- 41. (Original) The method according to Claim 33, further including the said disposing a finishing lubricant on the base textile prior to forming the flat and wrinkled regions.

Serial No.: 09/767,651 Inventor(s): Willauer et al.

42-66. (Cancelled)

U.S. PTO Customer No. 25280

Case No.: 5132